



外形尺寸 OUTER DIMENSIONS	EUW-120 EUW-120s	选项功能 OPTION FUNCTION
-----------------------	------------------	----------------------

A	Overall height		1890 (1950) mm
B	Overall length		2600 mm
C	Traverse stroke		1800 mm
D	Main-arm vertical stroke		1200 (1400) mm
E	Main-arm vertical standby		230 mm
F	Bottom of crosswise to chuck mount position		325 mm
G	Base side face- Box end		405 mm
H	Sub-arm Vertical standby	---	280 mm
I	Main-arm reach max		1200mm
J	Main-arm crosswise stroke max	800 mm	685mm
K	Main-arm crosswise standby min	280 mm	515 mm
L	Main/Sub-arm proximity min	---	250mm
M	Sub-arm crosswise stroke max	---	685mm
N	Sub-arm crosswise standby min	---	265 mm
O	Crosswise arm end- Box end		1740 mm

	Air nipper in chuck circuit	
	NT	-
	NT gate cutting on crossmember of moving	4
	Additional vacuum sensing unit	4 circuits
	Product gripping	4 circuits
	Mold close during ascend	-
	Rotation unit	-
	Ejector return link	12
	EUROMAP 12	67
	EUROMAP 67	-

- 当尺寸C是1200mm时，尺寸B为1890mm
- when dimension C is 1200 mm , B is 1890mm

- 当尺寸C是1400mm时，尺寸B为1950mm
- when dimension C is 1400mm , B is 1950mm

Feature and scope of the product does not guarantee the product attributes, only for reference. Our scope of delivery and services provided are based solely on the terms of delivery and services provided are based solely on the terms of the contract. Technical data and illustration are only for reference. We reserve the rights of changing.

TSD- 2021- 12

广东拓斯达科技股份有限公司
GUANGDONG TOPSTAR TECHNOLOGY CO.,LTD.

2

ADD : No.2 Chuangxin Road, Datanglang, Dalingshan Town, Dongguan City,
Guangdong Province.

TEL 0769- 8305 0999 FAX 0769- 8584 5562

Domestic Service Hotline **400-096-8005**

